



## **SUSPENDED HORIZONTAL OVERHEAD**

SHOWN WITH HOLDRITE® #424 (1/2") TUBING ISOLATORS.  
AVAILABLE IN: #425 (3/4") & #426 (1.0") TUBING.  
(ALSO AVAILABLE IN 25/50 PLENUM RATED (-S) & UL94V-2 FLAME RATED (-RR & -RB))  
MOUNTED ON A HOLDRITE® #121-DLS BRACKET.  
(THIS BRACKET CAN HANG FROM 1/4" OR 3/8" ROD)

THIS INFORMATION IS PROPRIETARY TO HUBBARD ENTERPRISES AND IS SUBJECT TO CHANGE WITHOUT NOTICE. ANY REPRODUCTION IN PART OR WHOLE WITHOUT THE WRITTEN PERMISSION OF HUBBARD ENTERPRISES IS PROHIBITED.

••••HUBBARD ENTERPRISES••••  
**HOLDRITE®**

*"Converting Makeshift Methods into Engineered Solutions"™*

2560 PROGRESS STREET / VISTA, CA 92081 / 800-321-0316 OR 760-744-6944 / FAX: 760-744-0507 / WWW.HOLDRITE.COM

50-005465-000, RevA (Suspended Horizontal Overhead with #42X & #121-DLS)