for Chemical

Compatibility

#304 Stainless Steel High Flow Rate Flexible Design 15", 18" or 24" Length 3/4" to 2" FIP EPDM Washer

QUICK FLEX™ Connector Advantages

Compares to Copper Corrugated Connectors

- · Large ID for Higher Flow Rate
- · No Need for Dielectric Unions
- Reduce Installation Costs
- Minimize Corrosion & Electrolysis
- · Extreme Flexibility
- Ideal for Close to the Wall or Unique Installations
- · Provide Added Flexibility in Seismic Zones

Compares to Copper Braided Connectors

- · Large ID for Higher Flow Rate
- · Will not Kink
- 3/4" to 2" Diameter Connector Available
- High Flexibility for Tight Turning Radius

CONNECTOR APPLICATIONS









TECHNICAL DATA

Chrome-Plated

Brass Nuts

- Meets ASME A112.18.6
- #304 Stainless Steel
- 125 Service/200 Max PSI
- 190° Temperature Rated
- IAPMO Listed

Model#	Description	Box Qty
QFC-7515	34" FIP x 34 " FIP x 15" Stainless Steel Water Heater Connector	35
QFC-7518	34" FIP x 34 " FIP x 18" Stainless Steel Water Heater Connector	35
QFC-7524	34" FIP x 34 " FIP x 24" Stainless Steel Water Heater Connector	35
QFC-17518	1" FIP x $3/4$ " FIP x 18" Stainless Steel Water Heater Connector	30
QFC-17524	1" FIP x $3/4$ " FIP x 24" Stainless Steel Water Heater Connector	30
QFC-0118	1" FIP x 1" FIP x 18" Stainless Steel Water Heater Connector	25
QFC-0124	1" FIP x 1" FIP x 24" Stainless Steel Water Heater Connector	25
QFC-11418	11/4" FIP x 11/4" FIP x 18" Stainless Steel Water Heater Connector	12
QFC-11218	1½" FIP x 1½" FIP x 18" Stainless Steel Water Heater Connector	10
QFC-0218	2" FIP \times 2" FIP \times 18" Stainless Steel Water Heater Connector	9



www.HOLDRITE.com (800) 321-0316

HOLDRITE® is a premier manufacturer and distributor of construction products for both residential and commercial markets.

We provide quality products and value-added services for the distributor, contractor, engineer, architect and home owner to ensure cost effective solutions.

HOLDRITE

NOW

BACK PANEL


SKU'S!

WATER HEATER AND EQUIPMENT ACCESSORIES

QUICK SHED™

- · Superior engineered design
- Meets code requirements
- Galvanized steel construction
- Protects outside water heater from weather and tampering
- Provides neat and orderly appearance
- Move water heater outside to increase inside space
- Easy assembly with basic tools
- · Screws provide secure installation
- Superior front panel design provides access door for service
- Air space crush zone packaging protects corners and transfers weight evenly across product during transportation
- Model -B includes back panel

Description	Box Qty
24" Shed Enclosure (24" x 74" x 24")	1
24" Shed Enclosure (24" \times 74" \times 24") with back panel	1
26" Shed Enclosure (26" x 74" x 26")	1
26" Shed Enclosure (26" x 74" x 26") with back panel	1
30" Shed Enclosure (30" x 74" x 30")	1
30" Shed Enclosure (30" x 74" x 30") with back panel	1
Vent Cap	1
	24" Shed Enclosure (24" x 74" x 24") 24" Shed Enclosure (24" x 74" x 24") with back panel 26" Shed Enclosure (26" x 74" x 26") 26" Shed Enclosure (26" x 74" x 26") with back panel 30" Shed Enclosure (30" x 74" x 30") 30" Shed Enclosure (30" x 74" x 30") with back panel



QUICK SHED™ VENT CAP

- · Allows air circulation
- Prevent excess heat accumulation
- Keeps most rain and weather out
- Ideal for electric water heaters

Model#	Description	Box Qty
QS-EVC	Vent Cap	1

QUICK STRAP®

Expansion Tank Mounting Brackets

- Secures tank to wall and takes weight load off pipes
 Galvanized and stainless steel construction
- Galvanizeu anu Stainless steel Construc
- \bullet QS-5 Supports tanks up to 9" diameter
- QS-12 Supports tanks from 9½" to 13" diameter
- Includes mounting bracket, (2) support straps, and $\#8 \times 1\frac{1}{2}$ mounting screws







QUICK STAND™

Equipment Platform

- Equipment stand, unassembled
- Galvanized steel construction
- Meets Codes
- $\bullet \, \text{Independently lab tested} \\$

Model#	Size	Box Qty
40-S-34-U	Up to 2,000 lbs. 34" x 34" top	1



OUICK STAND™ SUSPENDED PLATFORM

- CEILING MOUNT
- Cross Braces for seismic requirements
- •1" or 11/4", PVC drain fitting (MIP/Socket)
- For CPVC drain fitting add -C to model #.
- •#40-SWHP supports up to 20 gallons or 375 lbs.
- #50-SWHP supports up to 50 gallons or 600 lbs.
- •#60-SWHP supports up to 50 gallons or 750 lbs.

26½" x 26½" x 2½"

28½" x 28½" x 3"

Model#	Drain Pan Size	Box Qty	Pallet Qty
40-SWHP	21¼" x 21¼" x 2½"	1	10

1

10

10



QUICK STAND™ SUSPENDED PLATFORM

- CEILING MOUNT
- No Cross Brace

50-SWHP

60-SWHP

- •1" or 11/4", PVC or CPVC drain fitting (MIP/Socket)
- For CPVC drain fitting add -C to model #.
- •#40-SWHP-A supports up to 20 gallons or 375 lbs.
- #50-SWHP-A supports up to 50 gallons or 600 lbs.
- •#60-SWHP-A supports up to 50 gallons or 750 lbs.

• M Series has 11/4 Metal drain fitting

- #30-SWHP-M supports up to 20 gallons or 300 lbs.
- •#40-SWHP-M supports up to 20 gallons or 375 lbs.
- #50-SWHP-M supports up to 50 gallons or 600 lbs.
- •#60-SWHP-M supports up to 50 gallons or 750 lbs.

Model#	Drain Pan Size	Box Qty	Pallet Qty
40-SWHP-A	21¼" x 21¼" x 2½"	1	10
50-SWHP-A	26½" x 26½" x 2½"	1	10
60-SWHP-A	28½" x 28½" x 3"	1	10

Model#	Drain Pan Size	Box Qty	Pallet Qty
30-SWHP-M	24" x 24" x 4"	1	10
40-SWHP-M	21¼" x 21¼" x 2½"	1	10
50-SWHP-M	26½" x 26½" x 2½"	1	10
60-SWHP-M	28½" x 28½" x 3"	1	10



Model#	Drain Pan Size	Box Qty	Pallet Qty
40-SWHP-W	21¼" x 21¼" x 2½"	1	10
50-SWHP-W	26½" x 26½" x 2½"	1	10
60-SWHP-W	28½" x 28½" x 3"	1	10

QUICK STAND™ SUSPENDED PLATFORM

- WALL MOUNT
- •1" or 11/4", PVC or CPVC drain fitting (MIP/Socket)
- For CPVC drain fitting add -C to model #.
- #40-SWHP-W supports up to 20 gallons or 375 lbs.
- #50-SWHP-W supports up to 50 gallons or 600 lbs.
- •#60-SWHP-W supports up to 50 gallons or 750 lbs.

• M Series has 1" or 11/4" Metal drain fitting

- •#30-SWHP-WM supports up to 20 gallons or 300 lbs.
- •#40-SWHP-WM supports up to 20 gallons or 375 lbs.
- #50-SWHP-WM supports up to 50 gallons or 600 lbs.
- •#60-SWHP-WM supports up to 50 gallons or 750 lbs.

Model#	Drain Pan Size	Box Qty	Pallet Qty
30-SWHP-WM	24" x 24" x 4"	1	10
40-SWHP-WM	21¼" x 21¼" x 2½"	1	10
50-SWHP-WM	26½" x 26½" x 2½"	1	10
60-SWHP-WM	28½" x 28½" x 3"	1	10



OUICK PAN™

• Meets Code Requirements

or CPVC drain fitting

- Rolled edges for safety
- Aluminum pan with 1" PVC
- Use with gas or electric water heaters
- Now with a compact 1" Bulkhead Fitting
- Add -C to model # for 1" CPVC drain fitting

Model#	Description	Box Qty
QP-20	20" Aluminum Water Heater Pan with drain fitting	6
QP-22	22" Aluminum Water Heater Pan with drain fitting	6
QP-24	24" Aluminum Water Heater Pan with drain fitting	6
QP-26	26" Aluminum Water Heater Pan with drain fitting	6
QP-28	28" Aluminum Water Heater Pan with drain fitting	6
QP-30	30" Aluminum Water Heater Pan with drain fitting	6










MODEL#	IAPMO LISTED	CITY OF L.A. APPROVED	CALIFORNIA ACCEPTED
QUICK STRAP-50	✓	✓	✓
QUICK STRAP-50-D	✓	✓	✓
QUICK BELT-50-F	✓	✓	✓
QUICK STRAP-50-P	✓	✓	✓
QUICK STRAP-120	~	✓	✓



QUICK STRAP® DELUXE



- Powder-coated steel water heater strap with (2) safety caps
- Supports up to 80 gallon water heaters
- Customized label available with your company name

Model#	Size	Box Qty	Pallet Qty
QS-50-D	Up to 80 gal.	15	120



QUICK STRAP[®]

- The most tested and recognized water heater restraint
- Galvanized water heater strap in box
- QS-50, QS-50-P Supports up to 80 gallon water heaters
- QS-120 Supports up to 120 gallon water heaters

Model#	Size	Qty	Pallet Qty
QS-50	Up to 80 gal.	15/Box	120
QS-50-S	Up to 80 gal.	15/Box	120
QS-50-P	Up to 80 gal.	15/Bag	180
QS-120	Up to 120 gal.	12	60



OUICK BELT™

- The most tested and recognized water heater restraint
- Soft-belt style water heater strap
- •#QB-50-F supports up to 80 gallon water heaters

Model#	Size	Box Qty	Pallet Qty
QB-50-F	Up to 80 gal.	20	120



OUICK STAND™

- · Water heater stand, both assembled and unassembled
- Galvanized steel construction
- "-U" Models are unassembled. "-A" models are pre-assembled.

Model#	Size	Qty	Pallet Qty
40-S-22-U	Up to 52 gal. / 650 lbs.	1	24
40-S-22-A	Up to 52 gal. / 650 lbs.	1	24
40-S-24-U	Up to 100 gal. / 1,200 lbs.	1	18
40-S-24-A	Up to 100 gal. / 1,200 lbs.	1	18
40-S-30-U	Up to 100 gal. / 1,200 lbs.	1	12
40-S-34-U	Up to 2,000 lbs. 34" x 34" top	1	

